

10452

DOUBLE LED HEADS

DESCRIPTION

- Injection-Molded thermoplastic housing
- UL 94-5VA flame rating, fire retardant
- Super bright and Long Lasting LEDs
- Universal AC input voltage 120-347VAC
- Test switch and AC-ON indicator
- 2*1.2W lamps for emergency mode
- Universal Mounting: Wall/Ceiling Mounting
- 120 minutes battery backup time
- Suitable for damp locations
- Overcharge and over-discharge protection
- Operating temperature: 0°C ~ 40°C/32°F ~ 104°F
- 1-Year Warranty
- ULc Certified to C22.2-NO141-10


10452
BACKUP TIME
120

MINUTES APPROX.

RECHARGE TIME
24

HOURS

KEY FEATURES

Product Code	10452
Description	Emergency Light
Light Source	SMD2835 (24pcs)
Input Voltage	AC120-347V, 50/60Hz, 30mA
Input Power	2W
Emergency Power	2.4W
LED Heads	2 (1.2W each)
Luminance Flux	180lm
Emergency Duration	120 Minutes
Battery	Ni-Cd 3.6V, 120mAh
Recharge Times	24 Hrs
Remote Capable	N/A
Max. Mounting Height	10.4ft (3.1 m)
Instruction Sheet	VIEW

